

# CHIPPING HAMMERS

## CHIPPING HAMMERS Heavy Duty CH3 SERIES

- Offering the perfect balance of service life and economy
  - Powerful and hard hitting
  - Available in two different stroke lengths and two popular shank styles
  - Outside teasing throttle for safety and control
  - Saw tooth handle to cylinder connection for durability
- Standard Accessories:** Standard retainer (404313), Retainer spring (905842)



MOD. NO.	CH3H	CH4H	CH3R	CH4R
PROD. NO.	404323	404324	404328	404329

<b>Collar Type</b>	.580 Hex	.580 Hex	.680 Rnd.	.680 Rnd.
<b>Piston Dia. x Stroke</b>	1-1/8"x3	1-1/8"x4	1-1/8"x3	1-1/8"x4
<b>Blows per Minute</b>	1920	1500	1920	1500
<b>Overall Length</b>	14-7/8"	16-1/8"	14-7/8"	16-1/8"
<b>Weight (Lbs)</b>	14	15	14	15
<b>Avg. Air Con. (CFM)</b>	25	28	25	28
<b>Min. Hose Size</b>	1/2"	1/2"	1/2"	1/2"
<b>Air Inlet NPT</b>	3/8"	3/8"	3/8"	3/8"

## CHIPPING HAMMERS Super Duty JCO SERIES

- Powerful hard hitting industrial chipping hammers
- Available in three different stroke lengths
- Two popular shank styles - .580 Hex and .680 round shank with oval collar
- Drop forged, open handle design
- Outside teasing throttle
- Ring valve type
- Heat treated hardened steel piston and cylinder for long tool life



# RIVET BUSTER

## 11" RIVET BUSTER Heavy Duty

### RB11 404362

- 11" piston stroke for maximum hitting power
  - Suitable for cutting off bolts and large rivet heads and for heavy duty chipping work
  - Teasing throttle for increased control
  - Forged steel handle
  - Heat treated, hardened steel piston and cylinder
  - RB11 uses 1-1/8" tooling (Jumbo)
  - Piston stopper prevents piston from exiting the cylinder when retainer is removed
- Standard Accessories:** Retainer assembly



MOD. NO.	JCO-2H	JCO-3H	JCO-4H	JCO-2R	JCO-3R	JCO-4R	RB11
PROD. NO.	404307	404308	404309	404317	404318	404319	404362

<b>Collar Type</b>	.580 Hex	.580 Hex	.580 Hex	.680 Round	.680 Round	.680 Round	—
<b>Piston Dia. x Piston Stroke</b>	1-1/8" x 2"	1-1/8" x 3"	1-1/8" x 4"	1-1/8" x 2"	1-1/8" x 3"	1-1/8" x 4"	1-3/16" x 11"
<b>Blows per Minute</b>	2,500	2,300	1,700	2,500	2,300	1,700	625
<b>Overall Length</b>	12-3/4"	14-3/8"	16"	12-3/4"	14-3/8"	16"	26"
<b>Weight (Lbs.)</b>	15	16	17	15	16	17	33
<b>Avg. Air Consumption (CFM)</b>	29	31	33	29	31	33	38
<b>Min. Hose Size</b>	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"
<b>Air Inlet NPT</b>	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"
<b>Rivet Capacity</b>	—	—	—	—	—	—	1"

• FOR MAXIMUM PERFORMANCE WE RECOMMEND 90 LB PSI AIR PRESSURE

# CHIPPING HAMMER ACCESSORIES

PROD. NO.	MOD. NO.	Description
404313	CHR-1	Standard Retainer
404311	QCR-1	Quick Change Retainer
905801	JCO1191-2	Flat Spring with pin for QCR-1 retainer
905802	JCO1194-2	Heavy Duty Retainer Spring
905842	JCO194	Retainer Spring



404313



404311



905842

## CHIPPING HAMMER STEELS

### .580 HEX SHANK WITH OVAL COLLAR

Fits JET JCO-H and CH-H series chipping hammers and all other makes of .580 hex shank oval collar chipping hammers.



PROD. NO.	MOD. NO.	Description	Overall Length
408312	VF300H	Flat Chisel	12"
408331	VM230H	Moil Point	10"
408332	VM300H	Moil Point	12"
408352	VWF300H	Wide Flat Chisel	12"

### .680 ROUND SHANK WITH OVAL COLLAR

Fits JET JCO-R and CH-R series chipping hammers and all other makes of .680 round shank oval collar chipping hammers.



PROD. NO.	MOD. NO.	Description	Overall Length
408315	VF300R	Flat Chisel	12"
408335	VM300R	Moil Point	12"
408355	VWF300R	Wide Flat Chisel	12"



## ACCESSORIES FOR RIVET BUSTER

PROD. NO.	MOD. NO.	Description
905881	RB2190	2.565 Retainer for RB11
905882	RB2101	Upper Sleeve for RB11
905883	RB2103	Lower Sleeve for RB11
905884	RB2194	Retainer Spring for RB11
905893	RB2104-2	Rubber Bumper for RB11



## PAVING BREAKERS Heavy Duty

- Powerful heavy duty industrial paving breakers
- Large diameter smooth stroke piston
- Full control throttle
- Replaceable front head bushing
- Four bolt head to cylinder construction
- Efficient valve chest for low maintenance
- Drop forged cylinder
- Chisel retainer latch
- Rubber handle grips

**Optional Accessory:** Hose Swivel (404312), 7/8"-24 x 1/2" HB



404312

MOD. NO.	PB30-78	PB30-1	PB60-118	PB60-114	PB90-118	PB90-114
PROD. NO.	404703	404704	404705	404706	404708	404709
<b>Hex Shank Size</b>	7/8" x 3-1/4"	1" x 4-1/4"	1-1/8" x 6"	1"-1/4" x 6"	1-1/8" x 6"	1-1/4" x 6"
<b>Piston Dia. x Piston Stroke</b>	1-3/4" x 3-3/8"	1-3/4" x 3-3/8"	2-1/4" x 5"	2-1/4" x 5"	2-5/8" x 6-1/2"	2-5/8" x 6-1/2"
<b>Blows per Minute</b>	1,550	1,550	1,400	1,400	1,250	1,250
<b>Overall Length</b>	22-1/2"	22-1/2"	25-3/8"	25-3/8"	28-1/2"	28-1/2"
<b>Weight (Lbs.)</b>	33	33	66	66	92.5	92.5
<b>Avg. Air Consumption (CFM)</b>	49	49	58	58	77	77
<b>Min. Hose Size</b>	1/2"	1/2"	3/4"	3/4"	3/4"	3/4"

- 30 lb. class: Light-weight, heavy duty - minimum compressor 7-1/2 horsepower
- 60 lb. class: Medium weight, heavy duty - minimum compressor 10 horsepower
- 90 lb. class: Extra heavy duty - minimum compressor 10 horsepower
- **FOR MAXIMUM PERFORMANCE WE RECOMMEND 90 LB PSI AIR PRESSURE**