

SANDERS



5" HIGH SPEED SANDER

VS125A **403102**

- An excellent economical high speed sander
- Complete with 3", 4-1/2" and 5" backing plates
- Deluxe grip handle for comfortable operation
- Built-in power regulator
- Excellent for a variety of surface conditioning operations such as paint removal, light touch-up work, rust removal, etc.

Standard Accessories: 3" Backing plate (**905301**), 4-1/2" Backing plate (**905302**) and 5" Backing plate (**905303**); Holding tool (**905304**), Nut (**905305**)



Hardened, precision ground spiral bevelled gears

7" ANGLE SANDER Professional Duty

AS700HD **403109**

- Heavy duty construction for professional use
- Hardened, precision ground spiral beveled gears for long life & low vibration
- Insulated handle cover, contoured throttle lever and rear exhaust for operator comfort
- Side handle mounts on either side
- Excellent for heavy rust removal, metal sanding and contour work

Standard Accessories: Pad (**905306**), Nut (**905307**), Side Handle, Wrenches



7" VERTICAL SANDER

VS700C **403112**

- Double idler planetary gear system
- Ball bearing construction
- Built-in grease fitting for grease refill
- Light-weight and 2 handle design offers maximum operator control
- 4500 R.P.M. is ideal for rust removal and general sanding

Standard Accessories: Plastic pad (**905306**), Nut (**905307**), Side handle, Wrenches

JET Accessories



RESIN FIBRE SANDING DISCS

4" to 7" aluminum oxide discs are the standard of the metalworking industry and the most popular discs used for general metal removal. Please consult our abrasives catalogue for specifications.

MOD. NO. PROD. NO.	VS125A 403102	AS700HD 403109	VS700C 403112
Backing Disc Size	3" - 5"	7"	7"
Spindle Size	7/16" - 20	5/8" - 11NC	5/8" - 11NC
Free Speed R.P.M.	18,000	4,500	4,500
Overall Length	6"	15-1/2"	7-1/4"*
Weight (Lbs.)	2.5	6	5.5
Avg. Air Consumption (CFM)	6	13	6
Min. Hose Size	3/8"	3/8"	3/8"
Air Inlet NPT	1/4"	1/4"	1/4"
*Height			

• FOR MAXIMUM PERFORMANCE WE RECOMMEND 90 LB PSI AIR PRESSURE

SANDERS


ORBITAL SANDER Standard Duty

OS232 **403303**

- Compact palm-grip design allows one hand operation
- Dynamically balanced for minimum vibration
- Built-in regulator for positive speed control
- All ball bearing construction
- Ideal for finishing furniture and auto body repair
- Orbital action helps deliver a patternless finish

Standard Accessory: Pad assembly (905311)

Uses 3-3/4" x 9" abrasive strips



ORBITAL SANDER Professional Duty

OS37SG **403307**

- Heavy duty orbital sander with 3-2/3" x 7" pad, designed for professional use
- Front and rear handle design permits two handed operation for maximum comfort and control
- Self generated dust collection system for work place safety, includes hose and reusable dust collection bag
- Ball bearing construction for long service life
- Infinitely adjustable speed regulator
- Ergonomically shaped, full sized, handle with vinyl cover for operator comfort and control
- Muffled, rear exhaust outlet directs exhaust air away from the work piece
- Orbital sanding action helps deliver a pattern free finish

Standard Accessories: Reusable dust bag and hose, 3-2/3" x 7" PSA sanding pad (905315)

Optional Accessory: 3-2/3" x 7" hook and loop pad (905314)



OS37SG Self generated dust collection system

DUAL PISTON STRAIGHT LINE SANDER

BFS315D **403313**

- Deluxe two-piston body file
- Front and rear piston ride on needle bearings for precise, smooth performance
- Well-balanced design
- Easy-to-grip two handle design for maximum control
- High quality aluminum pad
- Ideal for body filing, shaping and levelling large flat surfaces

Standard Accessory: Pad assembly (905312)



Uses 2-3/4" x 17-1/2" abrasive strips

MOD. NO.	OS232	OS37SG	BFS315D
PROD. NO.	403303	403307	403313

Stroke	3/16"	3/16"	1"
Free Speed S.P.M.	7,000	7,000	2,200
Overall Length	6-3/4"	9-1/2"	16"
Weight (Lbs.)	4.4	4.6	6.25
Avg. Air Consumption (CFM)	6	20	8
Min. Hose Size	3/8"	3/8"	3/8"
Air Inlet NPT	1/4"	1/4"	1/4"

• FOR MAXIMUM PERFORMANCE WE RECOMMEND 90 LB PSI AIR PRESSURE

